SLIP RING SPECIFICATION FORM

To assist in specifying a slip ring assembly, please fill out the following form.
This form may also be found and completed at our web site (**www.fabricast.com**)
and sent directly to Fabricast via e-mail.

COMPANY _____ DATE _____
ADDRESS _____ PHONE( ) _____
_____ FAX ( ) _____
CONTACT _____ E-MAIL _____

1. APPLICATION _____

2. TYPE OF UNIT
( ) Self-Contained assembly
( ) Separate rotor and brush block assembly

3. TOTAL NUMBER OF ASSEMBLIES _____

4. ELECTRICAL REQUIREMENTS

Number of Rings	Description	Current (Amps)	Voltage (Volts)	Frequency / Data Rate	Other Requirements
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____
_____	_____	_____	_____	_____	_____

5. MECHANICAL REQUIREMENTS
Speed (RPM) _____ Duty Cycle _____
Inside (Bore) Diameter _____ Max. Outside Diameter _____
Max. Length _____ Lead Length & Type _____
Mounting: ( ) Shaft ( ) Housing
( ) Vertical ( ) Horizontal

6. OPERATING ENVIRONMENT
Temperature Range _____ Altitude _____
Special Atmospheres _____ Humidity _____
Vibration/Shock _____ Clean/Dirty _____
Other _____

7. REMARKS _____
_____
_____
_____

Fabricast, Inc.® *MANUFACTURER OF SLIP RING ASSEMBLIES*

TELEPHONE: (626) 443-3247
FAX: (626) 443-5594
E-MAIL: info@fabricast.com
WEB SITE: www.fabricast.com

P.O. BOX 3176, 2511 SEAMAN AVENUE, SOUTH EL MONTE, CALIFORNIA 91733

© 2009 FABRICAST, INC.